



The Haldex range of manual slack adjusters are permanently lubricated, yet are additionally equipped with a "grease nipple" for optional lubrication. The positive lock mechanism is protected from rust and corrosion by plating and shaft sealing.





Haldex Manual Slack Adjusters

Straight Arm - (Torque Rating 26,000 In. Lbs)



<i>Part Number</i>	<i>Arm Length</i>	<i>Spline Size</i>	<i>Pin Size</i>
KN44041	6.0"	1.60" x 37	.50"
KN44061	5.5", 6.5"	1.50" x 28	.50"
KN44071	5.0", 6.0", 7.0"	1.50" x 28	.50"
KN47001	5.0", 6.0", 7.0"	1.50" x 10	.50"
KN47011	5.5", 6.5"	1.50" x 10	.50"
KN52050	5.5"	1.50" x 48	.50"
KN55001	5.5"	1.25" x 24	.50"
100-001-721#	120,150,180, 220,250mm	1.50" x 10	14.0mm

= Torque Rating 24,000 In. Lbs

Curved Arm* - (Torque Rating 26,000 In. Lbs)


<i>Part Number</i>	<i>Arm Length</i>	<i>Spline Size</i>	<i>Pin Size</i>
KN51000	6.0"	1.50" x 10	.50"
KN51010	6.0"	1.50" x 28	.50"

Offset Arm* - (Torque Rating 26,000 In. Lbs)

<i>Part Number</i>	<i>Arm Length</i>	<i>Spline Size</i>	<i>Offset</i>
KN49000	4.5", 5.5"	1.25" x 10	RH .62"
KN49010	4.5", 5.5"	1.25" X 10	LH .62"
KN50000	4.5", 5.5"	1.50" X 10	RH. .62"
KN50010	4.5", 5.5"	1.50" X 10	LH .62"
KN50060	4.0", 5.0", 6.0"	1.50" X 10	RH .62"
KN50070	4.0", 5.0", 6.0"	1.50" X 10	LH .62"
KN53020	5.5"	1.50" X 28	RH .62"
KN53030	5.5"	1.50" X 28	LH .62"
104-501-050#	5.0", 6.0"	1.50" X 10	RH 1.5"
104-401-050#	5.0", 6.0"	1.50" X 10	LH 1.5"

= Torque Rating 24,000 In. Lbs




The above drawing illustrates the proper viewing angle to determine the right or left-hand offset of the slack adjuster.

Note: * = Unit is to be mounted with adjuster nut away from push rod only.

PBR Australia Pty Ltd
264 East Boundary Road
East Bentleigh Vic 3165

www.pbr.com.au
 Phone: (03) 9575 2200
 Fax: (03) 9575 2288